


The information contained in this drawing is the sole property of CWS Coil Winding Specialist. Any reproduction in part or whole without written permission of CWS Coil Winding Specialist is prohibited.

REVISION HISTORY					
REV	ECN	DESCRIPTION	SIGN & DATE		
			BY	DATE	CHK
B		PRODUCTION RELEASE	RRR	9/20/04	JLU



SCHEMATIC

- 6 ON TOP OF COVER
IF APPLICABLE, MARK PART NUMBER

- 5 TINNED TERMINALS



- 4 CONSTRUCTION:
TERMINAL TENSILE STRENGTH = 2.5 KG MIN.
INSTALL COVER AND ENCAPSULATE WITH EPOXY
TERMINATED LEAD SOLDERED TO TERMINAL PINS
WIND WIRE TO CORE, EVENLY SPACED

- 3 SPECIFICATIONS:
MIN. Q = 75
MAX DC RESISTANCE = 3.0 OHMS
WINDING WIRE SIZE = 0.16 MM
L = 1.2 mH ± 10 %, 25.2 KHZ
OPERATING TEMP = -20 °C TO +100 °C
MAX TEMP. RISE = 20 °C

- 2 CORE: POWER FERRITE DRUM CORE

- 1 MATERIAL: UL RECOGNIZED 94V-0 FOR FLAMMABILITY

NOTES: UNLESS OTHERWISE SPECIFIED,



QTY	CODE	MFG. P/N	DESCRIPTION	ITEM NO.
	IDENT			
PARTS LIST				
AUTOCAD		X	CWS Coil Winding Specialist.	
SOLIDWORKS			1510 E. Edinger Ave.	
SIGN		DATE	Unit B, Santa Ana, CA. 92705	
DRAW		9/20/04	Potted Radial Power Chokes	
RFR		9/20/04		
QDR		9/20/04		
JLU		9/20/04		
DGR		9/20/04	M1012-122K	
KSUM		9/20/04		
APPR		9/20/04		
JLU		9/20/04		
DO NOT SCALE DRAWING		SCALE	2=1	REV B