



The information contained in this drawing is the sole property of CWS Coil Winding Specialist. Any reproduction in part or whole without written permission of CWS Coil Winding Specialist is prohibited.


REVISION HISTORY

REV	ECN	DESCRIPTION	SIGN & DATE		
			BY	DATE	DATE
A		PRE-PRODUCTION RELEASE	TKK	4/10/04	4/12/04

VERTICAL CONFIGURATION



HORIZONTAL CONFIGURATION



- LEADS MUST BE TANGENT TO THE CORE
FLUSH WITH THE CORE EDGE, AS SHOWN
- 5 REMOVE INSULATION AND TIN LEADS


- 4 WIND COILS EVENLY SPACED
CONSTRUCTION:

- HI-POT TEST FOR CORE TO WINDING = 500 VDC
DCR = 12.6 MILLI-OHMS @ 25 °C
L = 5.6 UH ± 20% , 1 KHZ, 0.25 Vrms, 0 ADC.
3 SPECIFICATIONS: MAX DC CURRENT = 3 AMPS


- WIRE: UL RECOGNIZED 130° RATED MAGNET WIRE
CWS BYTEMARK OR OTHER APPROVED PART
- 2 CORE: MANGANESE ZINC FERRITE ROD

- RATING CLASS B (130°) REQUIRED
- 1 MATERIAL: WIRE INSULATION - UL RECOGNIZED 94V-0 FOR FLAMMABILITY
- NOTES: UNLESS OTHERWISE SPECIFIED, POWER INDUCTOR.
DIMENSIONS IN INCHES [MM]

MOUNTING HOLES PATTERN



MOUNTING HOLES PATTERN



CODE IDENT	MFG. P/N	DESCRIPTION	ITEM NO.
PARTS LIST			
AUTOCAD SIGN	X	COIL WS COM, INC WWW.COILWS.COM	
SOLIDWORKS SIGN	DATE	CWS Coil Winding Specialist. 1510 E. Edinger Ave. Unit B, Santa Ana, CA 92705	
DRAWN TDK	4/10/04	Power Chokes	
DESIGN JLAU	4/10/04		
ENGR. KSUN	4/10/04		
APPR. JLAU	4/12/04		
DO NOT SCALE DRAWING		SIZE 10X, 10X B	REV A
SCALE 2=1		PCRR0620-5R6M	
		SHEET 1 OF 1	