The information contained in this drawing is the sole property of CWS Coil Winding Specialist.
Any reproduction in part or whole without written permission of CWS Coil Winding Specialist is prohibited.

REVISION HISTORY						
REV	ECN	DESCRIPTION	SIGN & DATE			
			BY	DATE	CHK	DATE
A		PRODUCTION RELEASE	RPR	8/10/04	JLAU	8/10/04



SCHEMATIC



TOP VIEW



FRONT VIEW



MOUTING HOLES PATTERN

6 IF APPLICABLE, LABEL PART NUMBER AND VALUE

5 SOLDER WINDING TO TINNED LEADS

COVER WINDINGS WITH UL APPROVED PVC TUBING
WIND WIRES TO ROD CORE, EVENLY SPACED.

4 CONSTRUCTION:

SELF RESONANCE FREQUENCY (SRF) = 29 MHz
MAX DC CURRENT = 370 MILLI-AMPS
DCR = 1500 MILLI-OHMS MAX.
INDUCTANCE = 33.0 UH +-10% @ LOW DC BIAS, 1 KHz, 250mV

3 SPECIFICATIONS OF POWER INDUCTOR:

WIRE: UL RECOGNIZED 130°C RATED MAGNET WIRE
CWS BYTEMARK OR OTHER APPROVED PART

2 CORE: FERRITE ROD CORE, LOW LOSS MNZN

BOBBIN RATING CLASS B (130°C) REQUIRED

1 MATERIAL: UL RECOGNIZED 94V-0 FOR FLAMMABILITY

NOTES: UNLESS OTHERWISE SPECIFIED.

	CODE IDENT	MFG. P/N	DESCRIPTION	ITEM NO.

PARTS LIST

AUTOCAD		X
SOLIDWORKS		
SIGN		DATE
DRAWN	RPR	8/10/04
CHECKED	JLAU	8/10/04
ENGR.	KSUN	8/10/04
APPR.	JLAU	8/10/04

UNLESS OTHERWISE SPECIFIED
DIMENSIONING AND TOLERANCE PER ANSI Y14.5M
ALL DIMENSIONS ARE IN INCHES AND [MILIMETERS].
TOLERANCE INCHES: .XXX=±.005 .XX=±.015 ∠=±0°30'
TOLERANCE METRICS: .XXX=±.127 .XX=±.38 ∠=±0°30'
ANGLE PROJECTION
DO NOT SCALE DRAWING

COILWS COM, INC
WWW.coilws.com

CWS Coil Winding Specialist.
1510 E. Edinger Ave.
Unit B. Santa Ana, CA. 92705

TITLE: Power Inductor

SIZE B | DWG. NO. R0612-330K | REV A

SCALE 1=1 | SHEET 1 OF 1