



The information contained in this drawing is the sole property of CWS Coil Winding Specialist.
Any reproduction in part or whole without written permission of CWS Coil Winding Specialist is prohibited.




DIMENSIONAL TOLERANCES INCHES [MM]				
A MAX	B MAX	C MIN	D TYP	X REF
0.73 [18.54]	0.37 [9.40]	0.50 [12.70]	0.051 [1.30]	0.29 [7.37]

REVISION HISTORY						
REV	ECN	DESCRIPTION	SIGN & DATE			
			BY	DATE	CHK	DATE
B	—	MECH AND ELECT. SPECS CHANGE	KCL	7/25/12	AK	7/25/12
C	—	UPDATED SPEC.	TN	07/15/2020	JL	07/15/2020




FRONT VIEW



SIDE VIEW

DC BIAS TABLE

DC BIAS (AMP)	L@ 1KHz (REF)
0	5.8uH
2	5.7uH
4	5.5uH
6	5.4uH
8	5.2uH
10	5.1uH



MOUNTING HOLES PATTERN

7 BUILD TO RoHS COMPLIANCE AND LEAD FREE.

USING A PERMANENT MARKING METHOD
MARK PART NUMBER, REVISION AND DATE CODE

6 WRAP INDUCTOR WITH 3M # 79 OR EQUAL

5 (I.E. COIL MUST REST FLAT ON PCB). LEADS MUST BE TANGENT TO THE CORE
REMOVE INSULATION AND TIN LEADS 0.5 INCH, FLUSH WITH THE COIL EDGE

WIND COILS EVENLY SPACED AROUND THE CORE
CONSTRUCTION:

THESE SPECIFICATIONS ARE BASED ON LOW RIPPLE CURRENT

WEIGHT: 6 GRAMS TYPICAL

SRF: GREATER THAN 10MHz

RECOMMENDED AMBIENT OPERATING TEMP: -40°C TO 155°C

HI-POT TEST FOR WINDING TO CORE ISOLATION = 500VDC MIN.

INDUCTOR CURRENT RATING : 10 AMPS, 40°C TEMP. RISE WITH SOME AIR FLOW

DCR = 4.0 MILLI-OHMS MAX.

INDUCTOR DC BIAS: SEE TABLE ON THE RIGHT

INDUCTANCE = 5.6uH±15% @ 0 AMP DC BIAS, 1.0 KHz, 250mV

3 SPECIFICATIONS: @ 25°C:

2 WIRE: UL RECOGNIZED 200°C RATED MAGNET WIRE
CORE: POWDERED TOROIDAL CORE, CWS BYTE MARK OR OTHER APPROVED PART

1 MATERIAL: UL RECOGNIZED 94V-0 FOR FLAMMABILITY, RATING CLASS B (130°C MIN.) REQUIRED
ANY TOLERANCE. THIS DIM. CAN VARY A LITTLE FROM PART TO PART.

"TYP" IN DIM. TOL. TABLE REFERS TO A NON-CRITICAL TYPICAL (AVERAGE) DIM. WITHOUT
NOTES: UNLESS OTHERWISE STATED, READ NOTES FROM BOTTOM UP.

CAGE CODE: 5DME2

UNLESS OTHERWISE SPECIFIED	
DIMENSIONING AND TOLERANCE PER ANSI Y14.5M	
ALL DIMENSIONS ARE IN INCHES AND [MILLIMETERS].	
TOLERANCE INCHES: .XXX=±.005 .XX=±.015 <1=±0°30'	
TOLERANCE METRICS: .XXX=±.127 .XX=±.38 <1=±0°30'	
ANGLE PROJECTION	
DO NOT SCALE DRAWING	

CODE IDENT		MFG. P/N		DESCRIPTION		ITEM NO.	
PARTS LIST							
AUTOCAD		X		COILWS COM, INC www.coilws.com		CWS Coil Winding Specialist. 353 W. Grove Ave. Orange, CA 92865	
SOLIDWORKS							
SIGN		DATE		TITLE: TOROIDAL POWER INDUCTOR 5.6uH, 10 Amps, Vertical			
DRAWN		TDK 2/8/04					
CHECKED		JLAU 2/9/04					
ENGR.		KSUM 3/5/04					
APPR.		JLAU 3/6/04					
				SIZE DWG. NO.		REV	
				B HF127-5R6M-10.0AV		C	
				SCALE 2=1		SHEET 1 OF 1	