



The information contained in this drawing is the sole property of CWS Coil Winding Specialist. Any reproduction in part or whole without written permission of CWS Coil Winding Specialist is prohibited.



SCHEMATIC


DIMENSIONAL TOLERANCES INCHES [MM]					
A MAX	B MAX	C MIN	D TYP	E MIN/MAX	X REF
1.30 [33.02]	0.65 [16.51]	0.50 [12.70]	0.045 [1.14]	0.04-0.60 [1.02-1.52]	0.60 [15.4]

REVISION HISTORY					
REV	ECN	DESCRIPTION	SIGN & DATE		
			BY	DATE	CHK DATE
D	—	REVISE DIMENSIONAL TOLERANCE ADD RoHS COMPLIANCE	KLC	11/9/10	AK 11/9/10
E	—	UPDATED SPEC.	TN	07/11/2020	JL 07/11/2020



DC BIAS TABLE

DC BIAS (AMP)	L@ 1KHz (REF)
0	150uH
2	149uH
4	146uH
6	141uH
6.5	139uH



MOUNTING HOLES PATTERN

7 BUILD TO RoHS COMPLIANCE AND LEAD FREE.

USING A PERMANENT MARKING METHOD
MARK PART NUMBER, REVISION AND DATE CODE
WRAP INDUCTOR WITH 3M # 79 OR EQUAL

(I.E. COIL MUST REST FLAT ON PCB). LEADS MUST BE TANGENT TO THE CORE
REMOVE INSULATION AND TIN LEADS 0.75 INCH, FLUSH WITH THE COIL EDGE

WIND COILS EVENLY SPACED AROUND THE CORE
CONSTRUCTION:

THESE SPECIFICATIONS ARE BASED ON LOW RIPPLE CURRENT
WEIGHT: 50 GRAMS TYPICAL

INTERWINDING CAPACITANCE = 29.8pF @ SRF

SRF = 2.40MHz TYP

|Z| = 21 KILO-OHMS TYP @ SRF

RECOMMENDED AMBIENT OPERATING TEMP: -55°C TO 180°C

HI-POT TEST FOR WINDING TO CORE ISOLATION = 1250 VDC, 5 SEC.

CURRENT RATING : 6.5 AMPS, 40°C TEMP. RISE WITH SOME AIR FLOW

DCR = 38 MILLI-OHMS MAX.

INDUCTOR DC BIAS: SEE TABLE ON THE RIGHT

INDUCTANCE = 150uH±10% @ 0 AMP DC BIAS, 1.0 KHz, 250mV

3 SPECIFICATIONS: @ 25°C:

WIRE: UL RECOGNIZED 200°C RATED MAGNET WIRE
CORE: POWDERED TOROIDAL CORE, CWS BYTE MARK OR OTHER APPROVED PART

1 MATERIAL: UL RECOGNIZED 94V-0 FOR FLAMMABILITY, RATING CLASS H (180°C MIN.) REQUIRED
ANY TOLERANCE. THIS DIM. CAN VARY A LITTLE FROM PART TO PART.

"TYP" IN DIM. TOL. TABLE REFERS TO A NON-CRITICAL TYPICAL (AVERAGE) DIM. WITHOUT

NOTES: UNLESS OTHERWISE STATED, READ NOTES FROM BOTTOM UP.

CAGE CODE: 5DME2

CODE IDENT		MFG. P/N		DESCRIPTION		ITEM NO.	
PARTS LIST							
AUTOCAD		X		CWS Coil Winding Specialist. 1510 E. Edinger Ave. Unit B. Santa Ana, CA. 92705			
SOLIDWORKS							
SIGN		DATE		COILWS COM, INC www.coilws.com			
DRAWN		BJN 01/17/07		TITLE: TOROIDAL POWER INDUCTOR 150uH, 6.5 Amps, Vertical			
CHECKED		JLAU 01/17/07		SIZE DWG. NO. HF270-151M-6.5AV			
ENGR.		KSUM 01/17/07					
APPR.		JLAU 01/17/07					
		B		REV E			
		SCALE		2=1		SHEET 1 OF 1	

UNLESS OTHERWISE SPECIFIED			
DIMENSIONING AND TOLERANCE PER ANSI Y14.5M			
ALL DIMENSIONS ARE IN INCHES AND [MILLIMETERS].			
TOLERANCE INCHES: .XXX=±.005 .XX=±.015 <I=±0°30'			
TOLERANCE METRICS: .XXX=±.127 .XX=±.38 <I=±0°30'			
ANGLE PROJECTION			
DO NOT SCALE DRAWING			