




The information contained in this drawing is the sole property of CWS Coil Winding Specialist. Any reproduction in part or whole without written permission of CWS Coil Winding Specialist is prohibited.



SCHEMATIC


DIMENSIONAL TOLERANCES INCHES [MM]				
A MAX	B MAX	C MIN	D TYP	X REF
1.30 [33.02]	0.69 [17.50]	0.75 [19.05]	0.03 [0.80]	0.60 [15.24]

REVISION HISTORY					
REV	ECN	DESCRIPTION	SIGN & DATE		
			BY	DATE	CHK DATE
C	—	REVISED DIMENSIONS, DCR ADD RoHS COMPLIANCE		11/12/08	
D	—	UPDATED SPEC.	TN	07/16/2020	JL 07/16/2020



DC BIAS TABLE

DC BIAS (AMP)	L@ 1KHz (REF)
0	750uH
1	723uH
2	706uH
3	673uH



MOUNTING HOLES PATTERN

7 BUILD TO RoHS COMPLIANCE AND LEAD FREE.

USING A PERMANENT MARKING METHOD
MARK PART NUMBER, REVISION AND DATE CODE
WRAP INDUCTOR WITH 3M # 79 OR EQUAL

(I.E. COIL MUST REST FLAT ON PCB). LEADS MUST BE TANGENT TO THE CORE
REMOVE INSULATION AND TIN LEADS 0.75 INCH, FLUSH WITH THE COIL EDGE

WIND COILS EVENLY SPACED AROUND THE CORE
CONSTRUCTION:

THESE SPECIFICATIONS ARE BASED ON LOW RIPPLE CURRENT
WEIGHT: 50 GRAMS TYPICAL

INTERWINDING CAPACITANCE = 56pF TYP @ SRF

SRF = 778KHz TYP

|Z| = 71 KILO-OHMS TYP @ SRF

RECOMMENDED AMBIENT OPERATING TEMP: -40°C TO 125°C

HI-POT TEST FOR WINDING TO CORE ISOLATION = 500VDC MIN.

CURRENT RATING : 3.0 AMPS, 40°C TEMP. RISE WITH SOME AIR FLOW

DCR = 180.0 MILLI-OHMS MAX.

INDUCTOR DC BIAS: SEE TABLE ON THE RIGHT

INDUCTANCE = 750uH ± 10% @ 0 AMP DC BIAS, 1.0 KHz, 250mV

3 SPECIFICATIONS: @ 25°C:

WIRE: UL RECOGNIZED 200°C RATED MAGNET WIRE

CORE: POWDERED TOROIDAL CORE, CWS BYTE MARK OR OTHER APPROVED PART

1 MATERIAL: UL RECOGNIZED 94V-0 FOR FLAMMABILITY, RATING CLASS B (130°C MIN.) REQUIRED
ANY TOLERANCE. THIS DIM. CAN VARY A LITTLE FROM PART TO PART.

"TYP" IN DIM. TOL. TABLE REFERS TO A NON-CRITICAL TYPICAL (AVERAGE) DIM. WITHOUT

NOTES: UNLESS OTHERWISE STATED, READ NOTES FROM BOTTOM UP.

CAGE CODE: 5DME2

CODE IDENT		MFG. P/N	DESCRIPTION		ITEM NO.
PARTS LIST					
AUTOCAD	X		COILWS COM, INC www.coilws.com		
SOLIDWORKS					
SIGN		DATE	CWS Coil Winding Specialist. 1510 E. Edinger Ave. Unit B. Santa Ana, CA. 92705		
DRAWN	BJN	2/8/04	TITLE: TOROIDAL POWER INDUCTOR 750uH, 3.0 Amps, Vertical		
CHECKED	JLAU	2/9/0			
ENGR.	KSUM	3/5/04			
APPR.	JLAU	3/6/04			
SIZE		DWG. NO.		REV	
B		HF270-751M-3.0AV		D	
SCALE		2=1		SHEET 1 OF 1	

UNLESS OTHERWISE SPECIFIED	
DIMENSIONING AND TOLERANCE PER ANSI Y14.5M	
ALL DIMENSIONS ARE IN INCHES AND [MILLIMETERS].	
TOLERANCE INCHES: .XXX=±.005 .XX=±.015 <I=±0°30'	
TOLERANCE METRICS: .XXX=±.127 .XX=±.38 <I=±0°30'	
ANGLE PROJECTION	
DO NOT SCALE DRAWING	