



The information contained in this drawing is the sole property of CWS Coil Winding Specialist.
Any reproduction in part or whole without written permission of CWS Coil Winding Specialist is prohibited.



DIMENSIONAL TOLERANCES INCHES [MM]				
A MAX	B MAX	C MIN	D REF	X REF
1.350 [34.29]	.750 [19.05]	.500 [12.70]	.040 [1.02]	1.200 [30.48]



7 BUILD TO RoHS COMPLIANCE AND LEAD FREE.

USING A PERMANENT MARKING METHOD

MARK PART NUMBER AND REVISION, IF APPLICABLE

6 WRAP INDUCTOR WITH 3M # 79 OR EQUAL

5 (I.E. COIL MUST REST FLAT ON PCB). LEADS MUST BE TANGENT TO THE CORE
REMOVE INSULATION AND TIN LEADS 0.50 INCH, FLUSH WITH THE COIL EDGE, AS SHOWN

4 WIND COILS EVENLY SPACED AROUND THE CORE
CONSTRUCTION:

THESE SPECIFICATIONS ARE BASED ON LOW RIPPLE CURRENT

WEIGHT: 58 GRAMS TYPICAL

INTERWINDING CAPACITANCE = 38.9 pF TYP @ SRF

SRF = 1.36 MHz TYPICAL

|Z| = 22.6 KILO-OHMS TYP @ SRF

RECOMMENDED AMBIENT OPERATING TEMP: -40 °C TO 200°C

HI-POT TEST FOR WINDING TO CORE ISOLATION = 1250 VDC 10 SEC

CURRENT RATING : 6 AMPS, 40 °C TEMP. RISE WITH SOME AIR FLOW

DCR = 61.1 MILLI-OHMS MAX.

INDUCTOR DC BIAS: SEE TABLE ON THE RIGHT

INDUCTANCE = 330 uH ± 15% @ 0 AMP DC BIAS, 1.0 KHz, 300mV

3 SPECIFICATIONS @ 25°C :

2 WIRE: UL RECOGNIZED 200°C RATED MAGNET WIRE
CORE: POWDERED TOROIDAL CORE, CWS BYTE MARK OR OTHER APPROVED PART

1 MATERIAL: UL RECOGNIZED 94V-0 FOR FLAMMABILITY, RATING CLASS H (180°C MIN.) REQUIRED


ANY TOLERANCE. THIS DIM. CAN VARY A LITTLE FROM PART TO PART.

"TYP" IN DIM. TOL. TABLE REFERS TO A NON-CRITICAL TYPICAL (AVERAGE) DIM. WITHOUT

NOTES: UNLESS OTHERWISE STATED, READ NOTES FROM BOTTOM UP.



CAGE CODE: 5DME2

REVISION HISTORY						
REV	ECN	DESCRIPTION	SIGN & DATE			
			BY	DATE	CHK	DATE
A	—	INITIAL RELEASE	KLC	10/01/2010	AK	10/01/2010
A1	—	UPDATED SPECS.	JZ	11/24/2020	JL	11/24/2020



DC BIAS TABLE

DC BIAS (AMP)	L @ 1.0 KHz
0	336uH
2	325uH
4	303uH
6	274uH



MOUNTING HOLES PATTERN

CODE IDENT		MFG. P/N	DESCRIPTION		ITEM NO.
PARTS LIST					
AUTOCAD		X		COILWS.COM, INC www.coilws.com	CWS Coil Winding Specialist. 353 W Grove Ave Orange, CA. 92865
SOLIDWORKS					
SIGN		DATE			
DRAWN	KLC	10/01/2010	TITLE: TOROIDAL POWER INDUCTOR 330 uH, 6 Amps, Horizontal		
CHECKED	AK	10/01/2010			
ENGR.	KLC	10/01/2010			
APPR.	KLC	10/01/2010			
		SIZE	DWG. NO.		REV
		B	MF270-331M-6AH		A1
		SCALE	2=1		SHEET 1 OF 1

UNLESS OTHERWISE SPECIFIED	
DIMENSIONING AND TOLERANCE PER ANSI Y14.5M	
ALL DIMENSIONS ARE IN INCHES AND [MILLIMETERS].	
TOLERANCE INCHES:	
.XXX=±.005 .XX=±.015 <1/16=±0'30"	
TOLERANCE METRICS:	
.XXX=±.127 .XX=±.38 <1/16=±0'30"	
ANGLE PROJECTION	
DO NOT SCALE DRAWING	