



The information contained in this drawing is the sole property of CWS Coil Winding Specialist.
Any reproduction in part or whole without written permission of CWS Coil Winding Specialist is prohibited.



DIMENSIONAL TOLERANCES INCHES [MM]				
A MAX	B MAX	C MIN	D REF	Y REF
1.350 [34.29]	.750 [19.05]	.500 [12.70]	.040 [1.02]	0.600 [15.24]

REVISION HISTORY						
REV	ECN	DESCRIPTION	SIGN & DATE			
			BY	DATE	CHK	DATE
A	—	INITIAL RELEASE	KLC	10/01/2010	AK	10/01/2010
A1	—	UPDATED SPECS.	JZ	08/08/2020	JL	08/08/2020



DC BIAS TABLE

DC BIAS (AMP)	L @ 1.0 KHz
0	336uH
2	325uH
4	303uH
6	274uH

7 BUILD TO RoHS COMPLIANCE AND LEAD FREE.

USING A PERMANENT MARKING METHOD
MARK PART NUMBER AND REVISION, IF APPLICABLE,
WRAP INDUCTOR WITH 3M # 79 OR EQUAL



(I.E. COIL MUST REST FLAT ON PCB). LEADS MUST BE TANGENT TO THE CORE
REMOVE INSULATION AND TIN LEADS 0.50 INCH, FLUSH WITH THE COIL EDGE, AS SHOWN

4 CONSTRUCTION: WIND COILS EVENLY SPACED AROUND THE CORE

WEIGHT: 58 GRAMS TYPICAL
INTERWINDING CAPACITANCE = 38.21 pF TYP @ SRF
SRF = 1.42 MHz TYPICAL
|Z| = 20.97 KILO-OHMS TYP @ SRF
RECOMMENDED AMBIENT OPERATING TEMP: -40°C TO 200°C
HI-POT TEST FOR WINDING TO CORE ISOLATION = 1250 VDC 10 SEC
CURRENT RATING : 6 AMPS, 40°C TEMP. RISE WITH SOME AIR FLOW
DCR = 70.0 MILLI-OHMS MAX.
INDUCTOR DC BIAS: SEE TABLE ON THE RIGHT
INDUCTANCE = 336 uH ± 15% @ 0 AMP DC BIAS, 1.0 KHz, 300mV
SPECIFICATIONS: @ 25° C



WIRE: UL RECOGNIZED 200°C RATED MAGNET WIRE
CORE: HIGH POWDERED TOROIDAL CORE, CWS BYTE MARK OR OTHER APPROVED PART




1 MATERIAL: UL RECOGNIZED 94V-0 FOR FLAMMABILITY, RATING CLASS H (180°C MIN.) REQUIRED

ANY TOLERANCE. THIS DIM. CAN VARY A LITTLE FROM PART TO PART.

"TYP" IN DIM. TOL. REFERS TO A NON-CRITICAL TYPICAL (AVERAGE) DIM. WITHOUT

NOTES: UNLESS OTHERWISE STATED, READ NOTES FROM BOTTOM UP.

CAGE CODE: 5DME2



MOUNTING HOLES PATTERN

UNLESS OTHERWISE SPECIFIED	
DIMENSIONING AND TOLERANCE PER ANSI Y14.5M	
ALL DIMENSIONS ARE IN INCHES AND [MILLIMETERS].	
TOLERANCE INCHES: .XXX=±.005 .XX=±.015 <1=±0°30'	
TOLERANCE METRICS: .XXX=±.127 .XX=±.38 <1=±0°30'	
ANGLE PROJECTION	
DO NOT SCALE DRAWING	

CODE IDENT	MFG. P/N	DESCRIPTION	ITEM NO.
PARTS LIST			
AUTOCAD	X	COILWS COM, INC www.coilws.com	CWS Coil Winding Specialist. 353 WEST GROVE ORANGE, CA 92865
SOLIDWORKS			
SIGN	DATE		
DRAWN	KLC 10/01/2010		
CHECKED	AK 10/01/2010	TITLE: TOROIDAL POWER INDUCTOR 330 uH, 6 Amps, Vertical	SIZE DWG. NO. B MF270-331M-6AV
ENGR.	KLC 10/01/2010		
APPR.	KLC 10/01/2010		
SCALE		2=1	REV A1
		SHEET 1 OF 1	