



The information contained in this drawing is the sole property of CWS Coil Winding Specialist.
Any reproduction in part or whole without written permission of CWS Coil Winding Specialist is prohibited.




DIMENSIONAL TOLERANCES INCHES [MM]							
A MAX	B MAX	B1 MAX	C MIN	D REF	D1 REF	X REF	Y REF
1.58 [40.00]	1.40 [35.56]	0.90 [22.86]	0.21 [5.30]	0.06 [1.63]	0.05 [1.27]	1.20 [30.48]	0.70 [17.78]



SCHEMATIC




FRONT VIEW




SIDE VIEW

DC BIAS TABLE

DC BIAS (AMP)	L @ 1.0 KHz
0	194.2uH
5	176.4uH
10	138.7uH
12	121.3uH



BOTTOM VIEW



MOUNTING HOLES PATTERN

NC = NO CONNECTION

7 BUILD TO RoHS COMPLIANCE AND LEAD FREE.

USING A PERMANENT MARKING METHOD

MARK PART NUMBER AND REVISION, IF APPLICABLE,

EPOXY COIL TO HEADER



5 REMOVE INSULATION AND TIN LEADS 0.21 INCH, FLUSH WITH THE HEADER EDGE, AS SHOWN

4 CONSTRUCTION: WIND COILS EVENLY SPACED AROUND THE CORE

WEIGHT: 76 GRAMS TYPICAL

INTERWINDING CAPACITANCE = 29.74 pF TYP @ SRF

SRF = 2.17 MHz TYPICAL

|Z| = 7.14 KILO-OHMS TYP @ SRF

RECOMMENDED AMBIENT OPERATING TEMP: -40°C TO 130°C

HI-POT TEST FOR WINDING TO CORE ISOLATION = 500 VDC 10 SEC

CURRENT RATING : 12 AMPS, 40°C TEMP. RISE WITH SOME AIR FLOW

DCR = 17.0 MILLI-OHMS MAX.

INDUCTOR DC BIAS: SEE TABLE ON THE RIGHT

INDUCTANCE = 190 uH ± 15% @ 0 AMP DC BIAS, 1.0 KHz, 300mV

3 SPECIFICATIONS: @ 25° C



WIRE: UL RECOGNIZED 200°C RATED MAGNET WIRE

CORE: HIGH POWDERED TOROIDAL CORE, CWS BYTEMARK OR OTHER APPROVED PART

1 MATERIAL: UL RECOGNIZED 94V-0 FOR FLAMMABILITY, RATING CLASS F (180°C MIN.) REQUIRED

ANY TOLERANCE. THIS DIM. CAN VARY A LITTLE FROM PART TO PART.

"TYP" IN DIM. TOL. REFERS TO A NON-CRITICAL TYPICAL (AVERAGE) DIM. WITHOUT

NOTES: UNLESS OTHERWISE STATED, READ NOTES FROM BOTTOM UP.

CAGE CODE: 5DME2

UNLESS OTHERWISE SPECIFIED	
DIMENSIONING AND TOLERANCE PER ANSI Y14.5M	
ALL DIMENSIONS ARE IN INCHES AND [MILLIMETERS].	
TOLERANCE INCHES:	
.XXX ± .005 .XX ± .015 <1/16 ± .030	
TOLERANCE METRICS:	
.XXX ± .127 .XX ± .38 <1/16 ± .030	
ANGLE PROJECTION	
DO NOT SCALE DRAWING	

REVISION HISTORY				
REV	ECN	DESCRIPTION	SIGN & DATE	
			BY	DATE
A	—	INITIAL RELEASE	RLU	04/25/2005
A1	—	UPDATED MECH. SPEC. ON LEAD LENGTH	TN	05/25/2018
A2		UPDATED SPECS.	JZ	02/22/2021

CODE IDENT		MFG. P/N	DESCRIPTION		ITEM NO.
PARTS LIST					
AUTOCAD		X		CWS Coil Winding Specialist. 353 WEST GROVE ORANGE, CA 92865	
SOLIDWORKS					
SIGN		DATE		www.coilws.com	
DRAWN		RLU	04/25/2005	TITLE: OUTPUT CHOKE 190 uH, 12 Amps, Horizontal	
CHECKED		JLAU	04/25/2005		
ENGR.		JLAU	04/25/2005		
APPR.		KKSUM	04/25/2005		
				SIZE	DWG. NO.
				B	OPC-3-190-12H
				SCALE	2=1
				SHEET	1 OF 1
				REV	A2