





# Thermal and Electromagnetics simulation – Part # EEK55246-800M-85A-C – Current rated 85A @ 10kHz

Current 30% (25.5 A)  
No Airflow  
Natural convection






Current 75% ( 63.75A)  
40 W/ (m<sup>2</sup>K) or 3 m/s  
air flow.




# Thermal and Electromagnetics simulation – Part # EEK55246-800M-85A-C – Current rated 85A @ 10kHz


$L_d = 63.75 \text{ A}$ ,  $A_r = 40$       Multislice: Magnetic flux density norm (T)



Ld=63.75 A, Ar=40 Surface: Magnetic flux density norm (T) Arrow Volume: Current density



Slice: Magnetic flux density norm (T) Arrow Volume: Magnetic flux density



# Abbreviations

Ld	: Current rated Amps
Ar	: Airflow
W/m <sup>2</sup> .K	: Watts / Sq meter .Kelvin – Heat Convection rate
m/s	: Meter/ Second - Airflow
degC	: Temperature in Deg C
T	: Tesla – Magnetic Flux density
Temp	: Temperature
Temp max:	Temperature Maximum
Amb	: Ambient Temperature
Amps	: Ampere Load current.
Slice	: Sectional view

## Disclaimer :

- Simulation MODEL is an effective tool for evaluating product performance by simulation; however, it does not simulate product performance in all test environments and is not intended to be a replacement for testing of the actual device by means of a test board or otherwise.
- Simulation results are for reference purposes only; CUSTOMER shall perform thorough testing using the actual device.