



The information contained in this drawing is the sole property of CWS Coil Winding Specialist. Any reproduction in part or whole without written permission of CWS Coil Winding Specialist is prohibited.

REVISION HISTORY					
REV	ECN	DESCRIPTION	SIGN & DATE		
			BY	DATE	DATE
B		PRODUCTION RELEASE	JLU	7/13/06	7/13/06



SCHEMATIC



FRONT VIEW

SIDE VIEW

7 BUILT TO ROHS COMPLIANCE AND LEAD FREE.


6 WHERE SHOWN
IF APPLICABLE, MARK PART NUMBER AND REVISION
APPLY EPOXY TO SECURE COIL TO BOBBIN.

5 INSERT THROUGH BOBBIN AS OUTPUT LEADS
REMOVE WIRE INSULATION AND
WIND COILS EVENLY SPACED


4 CONSTRUCTION:
INDUCTANCE AT RATED CURRENT = 657.0 uH
MAX. TEMP RISE AT RATED CURRENT = 22 °C
RATED CURRENT MAX. = 4.0 AMPS DC
DCR = 104.0 MILLI-OHMS MAX
INDUCTANCE @ 0 ADC = 1200.0 uH±10%; 15.7KHz; 0.250 Vrms
SPECIFICATIONS @ 25°C:

3 WIRE: UL RECOGNIZED 155°C OR 200°C RATED MAGNET WIRE
CWSBYTEMARK OR OTHER APPROVED PART
CORE: COATED HIGH FLUX TOROID

2 RATING CLASS B (130°) REQUIRED
MATERIAL: UL RECOGNIZED 94V-0 FLAMMABILITY FOR BOBBIN
NOTES: UNLESS OTHERWISE SPECIFIED. READ FROM BOTTOM UP.



BOTTOM VIEW



MOUNTING HOLES PATTERN

CODE	IDENT	MFG. P/N	DESCRIPTION	ITEM NO.
PARTS LIST				
AUTOCAD	X			
SOLIDWORKS				
SIGN	DATE			
DRWN	7/13/06			
ENGR	7/13/06			
APPR	7/13/06			
KKSUM				
TITLE				
Output Choke				
4.0 Amps				
OFC-3-1200-4H				
REV B				
SHEET 1 OF 1				